

WHAT IS CLAIMED IS:

1. A method for supplying power to a device of a computer system,
comprising:
- 5 supplying power to the device from an integrated power supply;
determining whether the power supplied exceeds a threshold; and
if the threshold is exceeded, supplying power to the device from a non-
integrated power supply.
- 10 2. The method of claim 1, wherein if the threshold is exceeded the
integrated power supply supplies power up to the threshold and the non-integrated
power supply supplies any excess power.
- 15 3. The method of claim 1, wherein if the threshold is exceeded the non-
integrated power supply supplies all the power.
- 20 4. The method of claim 1, wherein high-power components on the device
are supplied power from the non-integrated power supply and low-power components on
the device are supplies power from the integrated power supply.
- 25 5. The method of claim 1, wherein the device is a bus-controlled component
and the integrated power supply is a bus slot capable of receiving the bus-controlled
component.
- 30 6. The method of claim 1, wherein a power sensor is used to determine
whether the threshold has been exceeded.
7. A bus power system for supplying power to a bus-controlled component,
comprising:
- a bus slot supplying power to the bus-controlled component; and
a bus power handling device for supplying power directly from a power
supply to the bus-controlled component if a bus slot power threshold is exceeded.

8. The bus power handling device of claim 7, wherein the bus power handling device is disposed between the bus slot and the bus-controlled component.

5 9. The bus power system of claim 7, wherein the bus power handling device is disposed on the bus-controlled component.

10 10. The bus power system of claim 8, further including a modified bracket attached to the bus-controlled component for securing the bus-controlled component within a computer case.

11. The bus power system of claim 7, further comprising a power sensor disposed on the bus power handling device that determines whether the bus slot power threshold has been exceeded.

15 12. A bus power handling device for supplying power to a bus-controlled component inserted into a bus slot supplying power to the component, comprising:
a power sensor that determines whether the bus slot has exceeded a power threshold; and
a power supply lead that supplies power from a power supply to the bus-
20 controlled component if the power threshold is exceeded.

25 13. The bus power handling device of claim 12, wherein the bus-controlled component obtains power from the bus slot until the power threshold is exceeded at which time the power is obtained from the power supply.

14. The bus power handling device of claim 12, wherein the bus-controlled component obtains power from the bus slot and any power in excess of the power threshold from the power supply.

30 15. The bus power handling device of claim 12, wherein the power threshold is a maximum power allowed by a computer bus standard for the bus slot.

16. The bus power handling device of claim 12, wherein bus slot supplies power to low-power devices on the bus-controlled component and the power supply

[illegible]